

# NOROO



Noroo	SATAjet 5000 B RP	SATAjet 5000 B HVLP	SATAjet 4000 B RP	SATAjet 4000 B HVLP	SATAjet 3000 B RP	SATAjet 100 B F RP
Primer Surface	1.4	--	1.4	--	1.4	1.6
	1.8 - 2.2 bar	--	1.8 - 2.2 bar	--	1.8 - 2.2 bar	2.0 - 2.2 bar
Base Coat (Solventborne)	1.3	1.3	1.3	1.3	--	--
	1.8 - 2.2 bar	1.8 - 2.2 bar	1.8 - 2.2 bar	1.8 - 2.2 bar	--	--
Base Coat(Waterborne)	1.2 / 1.3	1.2 / 1.3	1.2 / 1.3	--	--	--
	2.0 - 2.2 bar	2.0 - 2.2 bar	2.0 - 2.2 bar	--	--	--
Clear Coat	1.3 / 1.4	--	1.4	--	--	--
	1.8 - 2.2 bar	--	1.8 - 2.2 bar	--	--	--

<sup>1)</sup>Luftdüsendruck | air cap pressure | Pression à l'intérieur du chapeau d'air

\*Alle Angaben nach bestem Wissen und Gewissen aber ohne Gewähr. Bitte beachten Sie die Vorgaben des Lackherstellers. | Specifications in all conscience but without engagement. Please observe the paint manufacturer's requirements. |  
 Toutes indications sont en notre âme et conscience mais sans garantie. Veuillez respecter les instructions du fabricant de peinture. | Todos los datos según nuestro saber y entender, pero sin garantía. Tenga en cuenta las especificaciones del fabricante de pintura.